

[Get a Quote](#)

Overview

Fortinet FortiWiFi 60F - Security appliance - with 1 year 24x7 FortiCare Support + 1 year FortiGuard Unified Threat Protection (UTP) - GigE, 802.11ac Wave 2 - Wi-Fi 5 - 2.4 GHz, 5 GHz - desktop

Quick Specs

Figure 1 shows the appearance of FG-60F-BDL-950-12.



Table 1 shows the Quick Specs.

Product Code	FG-60F-BDL-950-12
Device Type	Security appliance
Bundled Services	1 year 24x7 FortiCare Support + 1 year FortiGuard Unified Threat Protection (UTP)
Frequency Band	2.4 GHz, 5 GHz
Status Indicators	Link/activity
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	17.2 Watt

Product Details

Figure 2 shows the front panel of FG-60F-BDL-950-12.



FG-60F-BDL-950-12 provides these features:

Compact and reliable form factor

Designed for small environments, you can place it on a desktop or wall mount it. It is small, lightweight yet highly reliable with superior MTBF, minimizing the chance of a network disruption.

High performance

Extends security to access layer to enable SD-branch transformation with accelerated and integrated switch and access point connectivity.

Secure SD-WAN

Consistent business application performance with accurate detection, dynamic WAN path steering and optimization. Simplification with zero touch deployment and centralized management with auto-provisioning, analytics and reporting.

Compare to Similar Items

Table 2 shows the comparison of FG-60F-BDL-950-12.

Module	FG-60F-BDL-950-12	FG-60F-BDL-950-36
Device Type	Security appliance	Security appliance
Bundled Services	1 year 24x7 FortiCare Support + 1 year FortiGuard Unified Threat Protection (UTP)	3 years 24x7 FortiCare Support + 3 years FortiGuard Unified Threat Protection (UTP)
Frequency Band	2.4 GHz, 5 GHz	2.4 GHz, 5 GHz
Status Indicators	Link/activity	Status
Voltage Required	AC 120/230 V (50/60 Hz)	AC 120/230 V (50/60 Hz)
Power Consumption Operational	17.2 Watt	18.7 Watt

Get More Information

Do you have any question about the **FG-60F-BDL-950-12**?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

FG-60F-BDL-950-12 Specification	
General	
Device Type	Security appliance
Bundled Services	1 year 24x7 FortiCare Support + 1 year FortiGuard Unified Threat Protection (UTP)
Width	8.5 in
Depth	6.3 in
Height	1.5 in
Processor / Memory / Storage	
Processors Installed	1 x Fortinet FortiASIC SOC4
Networking	
Form Factor	Desktop
Connectivity Technology	Wireless, wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac Wave 2

Network / Transport Protocol	IPSec
Frequency Band	2.4 GHz, 5 GHz
Status Indicators	Link/activity
Features	Firewall protection, antivirus analysis, Intrusion Prevention System (IPS), IPSec Virtual Private Network (VPN), fanless, web threat protection, CAPWAP support, application filtering
Encryption Algorithm	SSL, TLS 1.3
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
Expansion / Connectivity	
Interfaces	5 x 1000Base-T - RJ-45 2 x FortiLink - RJ-45 3 x 1000Base-T - RJ-45 (WAN / DMZ) 1 x console - RJ-45 1 x USB 3.0 - Type A
Miscellaneous	
Compliant Standards	UL, VCCI, C-Tick, cUL, CB, FCC
Power	
Power Device	External power adapter
Installed Qty	1
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	17.2 Watt
Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	10 - 90% (non-condensing)

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

● Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166

- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com